
GLASSvent® for Curtain Wall Order Form

(Order Form intended for standard GLASSvent. Contact Factory for custom applications.)

Ship to:	**Date of Order:**	**Billing Information/Quote #:**
	P.O. Number:	**Job Name:**
Sold to:	**Requested Ship Date:**	**Contact Name:**

PO Configuration:



(exterior view)

☐ Project Out


Standard Hardware:

☐ S.S. 4 - Bar Hinge & Cam Handle(s)

Options:

- ☐ Sub. Pole Ring Cam Handle(s)
- ☐ Sub. A/C (Custodial) lock(s)
- ☐ Sub. Concealed lock(s)
- ☐ Limit Stop
- ☐ Screen w/Wicket (Full wicket up to 20" tall / 9" wicket over 20" tall)
- ☐ Roto Operator w/Hook Bolt Locks
- ☐ Fixed screen (w/Roto only)

OSC Configuration:



(exterior view)

- ☐ LH Outswing Casement (Shown)
- ☐ RH Outswing Casement (Opposite)

Standard Hardware:

☐ S.S. 4 - Bar Hinge & Cam Handle(s)

Options:

- ☐ Sub. Pole Ring Cam Handle(s)
- ☐ Sub. A/C (Custodial) lock(s)
- ☐ Sub. Concealed lock(s)
- ☐ Screen w/Wicket (Full wicket up to 18" wide / 9" wicket over 18" wide)
- ☐ S.S. 4 - Bar Hinge, Sgl Handle Multi-point lock & Pole Ring
- ☐ Fixed screen (w/Multi-Point)

Finish:

_____

Design Windload:

_____ PSF

Glass Thickness:

☐ 1" ☐ Other: _____

Glazed:

- ☐ Open for Field Glazing
- ☐ Factory Glazed (MUST Specify Glass Type)

Glass Type: _____

Adaptor Type:

(System GLASSvent is being installed into)

1600 Systems	2250 Systems
☐ System 1	☐ 2250
☐ System 2	☐ 2250IG
☐ System 3	
☐ System 4	
☐ System 5	
☐ 1600 LR	

System / Adaptor requirements vary. Contact Factory for assistance in ordering.

Quantity & Sizes: Sizes based on framing DLO's?

☐ **YES** ☐ **NO** (If NO, describe dimensions in Special Instructions below)

	Quantity	Width	X	Height	Tag #'s
A)					
B)					
C)					
D)					
E)					
F)					

Special Instructions:

KAWNEER AN ALCOA COMPANY