
GLASSvent® for Storefront Order Form

Ship to:	Date of Order:	Billing Information/Quote #:
	P.O. Number:	Job Name:
Sold to:	Requested Ship Date:	Contact Name:

PO Configuration:

☐ Project Out



(exterior view)

Standard Hardware:

☐ S.S. 4 - Bar Hinge & Cam Handle(s)

☐ Full Wicket Screen

☐ 9" Wicket Screen

Options:

☐ Sub. Pole Ring Cam Handle(s)


☐ Sub. A/C (Custodial) lock(s)

☐ Sub. Concealed lock(s)

☐ S.S. 4 - Bar Hinge, Pivot shoe & Hook locks

☐ Fixed screen

OSC Configuration:



(exterior view)

☐ LH Outswing Casement (Shown)

☐ RH Outswing Casement (Opposite)

Standard Hardware:

☐ S.S. 4 - Bar Hinge & Cam Handle(s)

☐ Full Wicket Screen

☐ 9" Wicket Screen

Options:

☐ Sub. Pole Ring Cam Handle(s)

☐ Sub. A/C (Custodial) lock(s)

☐ Sub. Concealed lock(s)

☐ S.S. 4 - Bar Hinge, Sgl Handle Multi-point lock & Pole Ring

☐ Fixed screen

Quantity & Sizes:

☐ **Framing DLO's** ☐ **Actual Vent Sizes**

	Quantity	Width	X	Height	Tag #'s
A)					
B)					
C)					
D)					
E)					
F)					

Finish:

_____

Glass Thickness:

☐ 1/4"

☐ 1"

Glass Size Calculation
(Vent Width or Vent Height - 1.125")

Glazing by:

☐ Customer Glazed

☐ Factory Glazed

- ☐ Glass by Customer
- ☐ Glass by Kawneer

Limit Opening:

☐ **Not Required**

☐ 20 deg

☐ 30 deg

☐ 45 deg

☐ Other: _____

Adaptor Type:

☐ **Not Required**

☐ 400

☐ 450

☐ 451

☐ 451T

☐ Encore

☐ Other: _____

Comments:

OCTOBER 2009

KAWNEER
AN ALCOA COMPANY